

HEAT SHRINKABLE POLYOLEFIN

Product Description	Product Description (6" pcs.)	Inside Diameter Minimum as supplied (mm)	Inside Diameter Maximum after heating (mm)	Wall Thickness Maximum after heating (mm)	*Std. 4-ft Lengths ft / pkg	Std. Spools ft / spool	Std. 6-in Lengths pcs / pkg			
HIX-3/64	HIX6-3/64	0.046	(1.17)	0.023	(0.58)	0.016	(0.40)	100, 200	1000	40
HIX-1/16	HIX6-1/16	0.063	(1.60)	0.031	(0.79)	0.017	(0.43)	100, 200	1000	36
HIX-3/32	HIX6-3/32	0.093	(2.36)	0.046	(1.17)	0.020	(0.50)	100, 200	500	32
HIX-1/8	HIX6-1/8	0.125	(3.18)	0.063	(1.60)	0.020	(0.50)	100, 200	500	28
HIX-3/16	HIX6-3/16	0.188	(4.76)	0.093	(2.36)	0.020	(0.50)	100, 200	500	24
HIX-1/4	HIX6-1/4	0.250	(6.35)	0.125	(3.18)	0.025	(0.63)	100	250	20
HIX-3/8	HIX6-3/8	0.375	(9.53)	0.188	(4.76)	0.025	(0.63)	100	200	16
HIX-1/2	HIX6-1/2	0.500	(12.70)	0.250	(6.35)	0.025	(0.63)	20, 100	150	14
HIX-3/4	HIX6-3/4	0.750	(19.05)	0.375	(9.53)	0.030	(0.76)	20, 100	250	12
HIX-1"	HIX6-1"	1.000	(25.40)	0.500	(12.70)	0.035	(0.89)	20, 48	250	8
HIX-1-1/4	HIX6-1-1/4	1.250	(31.75)	0.625	(15.88)	0.040	(1.01)	20, 48	100	6
HIX-1-1/2	HIX6-1-1/2	1.500	(38.10)	0.750	(19.05)	0.040	(1.01)	20, 48	125	5
HIX-2	HIX6-2	2.000	(50.80)	1.000	(25.40)	0.045	(1.14)	20	125	3
HIX-3	HIX6-3	3.000	(76.20)	1.500	(38.10)	0.050	(1.27)	8, 24	50	2
HIX-4	HIX6-4	4.000	(101.60)	2.000	(50.80)	0.055	(1.40)	8, 24	50	1
HIX-5	N/A	5.000	(127.00)	2.500	(63.50)	0.060	(1.52)	8	50	N/A

- Standard Operating Temperature: -55°C to 135°C
- 2:1 shrink ratio
- Minimum shrink temperature: 121°C
- Provided in 4-foot, or 6-inch lengths, or on spools
- Standard colors are black, white, red, blue, yellow, green, and clear

APPLICATIONS

HIX is the most popular general purpose heat-shrinkable tubing used for insulating, jacketing, bundling, and identification. HIX is mechanically tough and has good abrasion and solvent resistance. Longitudinal shrinkage is less than 6%.

MINI HEAT GUN II® & HEAT SHRINK TUBING KIT

The **MINI HEAT GUN II** is ICO RALLY's most compact and lightweight UL Recognized heat gun. Powered by standard 110V AC power, it boasts a nozzle temperature of 610°F. When not in use, you can hang the **MINI HEAT GUN II** out of your way with its convenient workbench storage loop.

The heat gun is sold as a kit with 60, six-inch pieces of our most popular HIX heat shrink tubing. Sizes include 1/8", 3/16", 1/4", 3/8", and 1/2" (assorted colors).

The ICO RALLY part number for the **MINI HEAT GUN II** & Heat Shrink Tubing Kit is IR-25252.

